# SILICONES, INC.

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME: GI-384B** 

**SECTION I - PRODUCT IDENTIFICATION** 

MANUFACTURER: Information Phone: 336/886-5018

Silicones, Inc. Emergency Phone: CHEMTREC

P. O. Box 363 800/424-9300

211 Woodbine St. High Point, NC 27261

PRODUCT NAME: GI-384B

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

<u>INGREDIENTS</u> <u>CAS #</u> <u>EXPOSURE LIMITS</u>

None known to date.

\_\_\_\_\_

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N.A.\* SPECIFIC GRAVITY: 1.1
VAPOR PRESSURE (mm Hg.): N.A. MELTING POINT: N.A.

SYLPORATION RATE (Ruty)

VAPOR DENSITY (AIR=1): N.A. EVAPORATION RATE (Butyl Acetate=1): N.A.

SOLUBILITY IN WATER: Negligible

APPEARANCE AND ODOR: White to off-white liquid. Essentially odorless.

\_\_\_\_\_

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Greater than 210 °F FLAMMABLE LIMITS: N.A. LEL: N.A.

(ASTM D-3278) UEL: N.A.

EXTINGUISHING MEDIA: Carbon dioxide, sand, foam, dry chemicals

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear full protective clothing, including self-contained breathing apparatus.

- 1 -

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known to date.

<sup>\*</sup> N.A. throughout this document represents "Not Applicable".

PRODUCT NAME: GI-384B

- 2 -

### **SECTION V - REACTIVITY DATA**

STABILITY: **STABLE** 

CONDITIONS TO AVOID: N.A.

INCOMPATIBILITY (materials to avoid): Strong bases will cause depolymerization. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon dioxide, silicon dioxide.

WILL NOT OCCUR HAZARDOUS POLYMERIZATION:

CONDITIONS TO AVOID: N.A.

### **SECTION VI - HEALTH HAZARD DATA**

**ROUTES OF ENTRY:** INHALATION? NO SKIN? YES INGESTION? NO HEALTH HAZARDS (acute & chronic): May cause temporary, reversible eye irritation.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

SIGNS AND SYMPTOMS OF EXPOSURE: None known to date.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to date.

EMERGENCY AND FIRST AID PROCEDURES: Eye Contact: Flush eyes with large quantities of water for at

least 15 minutes. Consult a physician.

# SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Cover spill with an absorbent material such as sand or sawdust. Scoop up and place in an appropriately marked container.

WASTE DISPOSAL METHOD: May be incinerated or land-filled under conditions complying with federal, state, and local environmental control regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store at temperatures between 32 and 80 °F. OTHER PRECAUTIONS: N.A.

### **SECTION VIII - CONTROL MEASURES**

RESPIRATORY PROTECTION: Not required.

**VENTILATION:** LOCAL EXHAUST: N.A. SPECIAL: N.A.

> MECHANICAL: N. A. OTHER: N.A.

PROTECTIVE GLOVES: Rubber EYE PROTECTION: Safety goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Rubber apron, eye wash fountain, safety shower.

WORK/HYGIENIC PRACTICES: Wash hands immediately after use.

PREPARED BY: DJ DATE: 6/2/2000

# SILICONES, INC.

# MATERIAL SAFETY DATA SHEET

**PRODUCT NAME: GI-384A** 

**SECTION I - PRODUCT IDENTIFICATION** 

MANUFACTURER: Information Phone: 336/886-5018

Silicones, Inc. Emergency Phone: CHEMTREC

P. O. Box 363 800/424-9300 211 Woodbine St.

High Point, NC 27261

PRODUCT NAME: GI-384A

# SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

**INGREDIENTS EXPOSURE LIMITS** CAS #  $0.1 \text{ mg/m}^3 \text{ as tin}$ Organo-tin compounds Polymeric ethyl silicate 68412-37-3 N.A. Phenyltrimethoxysilane 02996-92-1 N.A. Octyltriethoxysilane 002943-75-1 N.A.

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N.A..\* SPECIFIC GRAVITY: 0.99 VAPOR PRESSURE (mm Hg.): N.A. MELTING POINT: N.A.

VAPOR DENSITY (AIR=1): N.A. EVAPORATION RATE (Butyl Acetate=1): N.A.

SOLUBILITY IN WATER: Slight

APPEARANCE AND ODOR: Red liquid. Mild alcohol-like odor.

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 230 °F FLAMMABLE LIMITS: N.A. LEL: N.A. (ASTM D-1310, Open Cup) UEL: N.A.

EXTINGUISHING MEDIA: Carbon dioxide, sand, foam, dry chemicals

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear full protective clothing, including selfcontained breathing apparatus.

- 1 -

UNUSUAL FIRE AND EXPLOSION HAZARDS: Organo-tin fumes may be evolved.

<sup>\*</sup> N.A. throughout this document represents "Not Applicable".

- 2 -

#### SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: N.A.

INCOMPATIBILITY (materials to avoid): Acids, bases and water.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Ethanol, silicon dioxide, carbon dioxide, and organo-

tin compounds.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: N.A.

#### SECTION VI - HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION? YES SKIN? YES INGESTION? NO

HEALTH HAZARDS (acute & chronic): Eye and skin irritant. Temporary irritation of respiratory tract may

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO SIGNS AND SYMPTOMS OF EXPOSURE: Overexposure via inhalation or skin absorption may cause headache and nausea. May irritate eyes and skin on contact. Inhalation of vapors may irritate the respiratory tract. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to date.

EMERGENCY AND FIRST AID PROCEDURES: Eye Contact: Flush eyes with large quantities of water for at least 15 minutes. Consult a physician. Skin Contact: Wash thoroughly with mild soap and water. Remove contaminated clothing. Inhalation: Remove to fresh air.

#### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Cover spill with an absorbent material such as sand or sawdust. Scoop up and place in an appropriately marked container.

WASTE DISPOSAL METHOD: May be incinerated or land-filled under conditions complying with federal, state, and local environmental control regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly closed and air-tight. Protect from moisture. Store in temperatures less than 80 °F. Store away from food and beverages.

OTHER PRECAUTIONS: Blanket vapor space with nitrogen for prolonged storage.

## **SECTION VIII - CONTROL MEASURES**

RESPIRATORY PROTECTION: If TLV is exceeded, use MSHA/NIOSH organic vapor respirator.

VENTILATION: LOCAL EXHAUST: Preferred SPECIAL: N.A.

MECHANICAL: Acceptable OTHER: N.A.

PROTECTIVE GLOVES: Rubber EYE PROTECTION: Safety goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Rubber apron, eye wash fountain, safety shower.

WORK/HYGIENIC PRACTICES: Wash hands immediately after use.

PREPARED BY: DJ DATE: 6/2/2000