SILICONES, INC.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: GI-650B

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER: Information Phone: 336/886-5018

Silicones, Inc. Emergency Phone: CHEMTREC P. O. Box 363 1-800-424-9300 211 Woodbine St.

High Point, NC 27261

PRODUCT NAME: GI-650B

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENTS EXPOSURE LIMITS CAS #

None known to date.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N.A.* SPECIFIC GRAVITY: 1.09 VAPOR PRESSURE (mm Hg.): N.A. MELTING POINT: N.A.

EVAPORATION RATE (Butyl Acetate=1): N.A. VAPOR DENSITY (AIR=1): N.A.

SOLUBILITY IN WATER: Negligible

APPEARANCE AND ODOR: White to buff colored. Essentially odorless.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Greater than 210 deg. F FLAMMABLE LIMITS: N.A. LEL: N.A.

(ASTM D-3278) UEL: N.A.

EXTINGUISHING MEDIA: Carbon dioxide, Sand, Foam, Dry Chemicals

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear full protective clothing, including selfcontained breathing apparatus.

- 1 -

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known to date.

^{*} N.A. throughout this document represents "Not Applicable".

PRODUCT NAME: GI-650B

- 2 -

SECTION V - REACTIVITY DATA

STABILITY: **STABLE**

CONDITIONS TO AVOID: N.A.

INCOMPATIBILITY (materials to avoid): Strong bases will cause depolymerization. HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Carbon dioxide, silicon dioxide.

WILL NOT OCCUR HAZARDOUS POLYMERIZATION:

CONDITIONS TO AVOID: N.A.

SECTION VI - HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION? NO SKIN? YES INGESTION? NO

HEALTH HAZARDS (acute & chronic): May cause temporary, reversible eye irritation.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

SIGNS AND SYMPTONS OF EXPOSURE: None known to date.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to date.

EMERGENCY AND FIRST AID PROCEDURES: Eye Contact: Flush eyes with large quantities of water for at

least 15 minutes. Consult a physician.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Cover spill with an absorbent material such as sand or sawdust. Scoop up and place in an appropriately marked container.

WASTE DISPOSAL METHOD: May be incinerated or land-filled under conditions complying with Federal, State, and Local environmental control regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store at temperatures between 32 and 80 deg. F

OTHER PRECAUTIONS: N.A.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: Not required.

VENTILATION: LOCAL EXHAUST: N.A. SPECIAL: N.A.

> MECHANICAL: N. A. OTHER: N.A.

PROTECTIVE GLOVES: Rubber EYE PROTECTION: Safety Goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Rubber apron, eye wash fountain, safety shower.

WORK/HYGIENIC PRACTICES: Wash hands immediately after use.

PREPARED BY: DJ DATE: 5/20/98

SILICONES, INC.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: GI-650A

SECTION I - PRODUCT IDENTIFICATION

MANUFACTURER: Information Phone: 336/886-5018 Silicones, Inc. Emergency Phone: CHEMTREC

P. O. Box 363

Emergency Phone: CHEMTREC

1-800-424-9300

211 Woodbine St. High Point, NC 27261

PRODUCT NAME: GI-650A

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

INGREDIENTS CAS # EXPOSURE LIMITS

Organo tin compounds $0.1 \text{ mg/m}^3 \text{ as tin}$

Ethyl silicate 78-10-4 10 ppm Polymeric ethyl silicate 68412-37-3 N.A.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N.A.* SPECIFIC GRAVITY: 0.99 VAPOR PRESSURE (mm Hg.): N.A. MELTING POINT: N.A.

VAPOR DENSITY (AIR=1): N.A. EVAPORATION RATE (Butyl Acetate=1): N.A.

SOLUBILITY IN WATER: Slight

APPEARANCE AND ODOR: Blue liquid. Mild alcohol-like odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 208 deg. F FLAMMABLE LIMITS: N.A. LEL: N.A. (ASTM D-3278) UEL: N.A.

EXTINGUISHING MEDIA: Carbon dioxide, Sand, Foam, Dry Chemicals

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear full protective clothing, including self-contained breathing apparatus.

- 1 -

UNUSUAL FIRE AND EXPLOSION HAZARDS: Organo tin fumes may be evolved.

^{*} N.A. throughout this document represents "Not Applicable".

PRODUCT NAME: GI-650A

- 2 -

SECTION V - REACTIVITY DATA

STABILITY: **STABLE**

CONDITIONS TO AVOID: N.A.

INCOMPATIBILITY (materials to avoid): Acids, bases and water.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Ethanol, silicon dioxide, carbon dioxide, and organo-

tin compounds.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: N.A.

SECTION VI - HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION? YES SKIN? YES INGESTION? NO

HEALTH HAZARDS (acute & chronic): Eye and skin irritant. Temporary irritation of respiratory tract may occur

CARCINOGENICITY: NTP? NO

IARC MONOGRAPHS? NO

OSHA REGULATED? NO

SIGNS AND SYMPTONS OF EXPOSURE: Overexposure via inhalation or skin absorbtion may cause headache and nausea. May irritate eyes and skin on contact. Inhalation of vapors may irritate the respiratory tract.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None known to date.

EMERGENCY AND FIRST AID PROCEDURES: Eye Contact: Flush eyes with large quantities of water for at least 15 minutes. Consult a physician. Skin Contact: Wash thoroughly with mild soap and water. Remove contaminated clothing. Inhalation: Remove to fresh air.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Cover spill with an absorbent material such as sand or sawdust. Scoop up and place in an appropriately marked container.

WASTE DISPOSAL METHOD: May be incinerated or land-filled under conditions complying with Federal, State, and Local environmental control regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep containers tightly closed and air-tight. Protect from moisture. Store in temperatures less than 80 deg. F. Store away from food and beverages.

OTHER PRECAUTIONS: Blanket vapor space with nitrogen for prolonged storage.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: If TLV is exceeded, use MSHA/NIOSH organic vapor respirator.

VENTILATION: LOCAL EXHAUST: Preferred SPECIAL: N.A.

> MECHANICAL: Acceptable OTHER: N.A.

PROTECTIVE GLOVES: Rubber EYE PROTECTION: Safety Goggles

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Rubber apron, eye wash fountain, safety shower.

WORK/HYGIENIC PRACTICES: Wash hands immediately after use.

PREPARED BY: DJ DATE: 5/20/98